

CITILÄ®

THE WINDSCREEN THAT RISES ABOVE THE AVERAGE



Balcony in Norway



Terrace in Norway



Villa in Stockholm, Sweden


## Height adjustable balcony glazing

Make better use of your balcony with Cit i Lä® height adjustable balcony glazing. With Cit i Lä®, you have the option of an open balcony when the weather is nice and sunny. Just raise up the adjustable screens when you need protection from harsh weather and cold winds.

This unique balcony glazing system is designed to make it easy and flexible to use and can be raised and lowered with a simple grip. As an option, it can be provided with overhead fixed glass up to the ceiling for completely glassed-in balcony. Cit i Lä® is also available electrically operated.

Made from aluminium, the standard design is equipped with laminated glass, both in the lower fixed part and in the height-adjustable part.

Fully open or glassed-in balcony? With **CITILÄ®** you can have both.




## EXAMPLE OF VERSIONS



Lowered position  
with glass



Raised position  
with glass



Raised position  
with translucent fixed  
and overhead glass

## TECHNICAL SPECIFICATIONS

|                           |  |
|---------------------------|--|
| WIDTH                     | Maximum 2200 mm per section  |
| HEIGHT                    | Standard heights* exclusive overhead fixed glass (lowered/raised position): <ul style="list-style-type: none"> <li>• 800/1300 mm</li> <li>• 900/1500 mm</li> <li>• 1000/1700 mm</li> <li>• 1100/1900 mm</li> <li>• 1200/2100 mm (maximum width 2000 mm)</li> </ul> <p>*Above ground level, a minimum height of 1100 mm might be required</p> |
| THICKNESS<br>GLASS/BOARDS | 90 mm<br>5 mm laminated glass in the moving part. In standard performance the lower fixed part is supplied with 6 mm laminated glass but it can be supplied with translucent glass or other materials.   |
| SURFACE COATING           | Satin anodized aluminium is the standard coating. Others surface coatings are available at an additional cost, such as powder coating or anodizing in other colours.   |
| INSTALLATION              | There are several types of attachments for installation against existing environment. There are also several connectors for corner and wall attachment. All connectors and feet are stainless steel.<br>Visit <a href="http://www.svalson.com">www.svalson.com</a> for more information.   |
| OPTIONS                   | Automatic locking at optional height.<br>Lock with key for raised position.<br>Overhead fixed glass.<br>Electrically operated.   |
| MANUFACTURED BY           | Svalson AB, Sweden   |

